

# Specifications

Model		M4N-071 4WD ROPS NARROW	M5N-091 / 111 4WD ROPS NARROW
<b>Engine</b>			
Type (make: Kubota)		V3800-CR-TIEF4 – Direct Injection, water-cooled 4-cycle diesel, Common Rail System, Turbocharger, DPF, DOC	V3800-CR-TIEF4 – Direct Injection, water-cooled 4-cycle diesel, Common Rail System, Turbocharger, Intercooler, DPF, DOC, SCR
Number of cylinders / Aspiration		4 / Turbocharged	
Rated engine HP (97/68/EC)	HP (kW)	72.6 (54.1)	92.5/105.7 (69.0/78.8)
PTO power @rated engine RPM (OECD CODE2) 12-speed / 24-speed	HP (kW)	61 (45.5)	78/91 (58.1/67.9) / 75/88 (55.9/65.6)
Rated engine	rpm	2400	
Fuel tank capacity	gal. (ℓ)	20.1 (76)	
Alternator	Amp	100	80
<b>Transmission</b>			
No. of speeds		F12 × R12 (opt. Creep F18 × R18)	F12 × R12 (opt. Creep F18 × R18) / F24 × R24 (opt. Creep F36 × R36)
Main gear shift		6-speed 2 ranges	6-speed 2 ranges with Hi-Lo
Shuttle shift		Electro-hydraulic	
<b>PTO</b>			
Type		Electro-hydraulic	
Speed	rpm	540/540E	
<b>Hydraulics</b>			
Pump capacity (3-point hitch)	gpm (ℓ/min.)	16.7 (63.3)	
3-point hitch / Category		Rigid lower link, easy adjust stabilizers / II	
Control system		Position, draft (top link sensing)	
Lift capacity at 24 in. behind lift point (SAE)	lbs. (kg)	3307 (1500)	
Lift capacity at 24 in. behind lift point (OECD)	lbs. (kg)	2976 (1350)	
No. of standard remote valves		2 with flow control (max. 5)	
<b>Other features</b>			
Front drive system		Electronic 4WD engagement with Bi-Speed	
Deck type (rubber-mounted w/ rubber mat)		Semi-flat	
<b>Standard tire size</b>			
Front		8 – 16	
Rear		12.4 – 24	
<b>Dimensions &amp; weight</b>			
Overall height (top of hood)	in. (mm)	54.7 (1390)	59.8 (1520)
Min. overall width*	in. (mm)	51.6 (1310)	53.5 (1360)
Ground clearance	in. (mm)	11.4 (290)	
Tread width	Front in. (mm)	41.3 (1050)	43.3 (1100)
	Rear in. (mm)	37.2 – 54.5 (945 – 1385)	
Tractor weight	lbs. (kg)	5049 (2290)	5357 (2430)

\* from right side front tire to left side step

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



©2017 Kubota Corporation

# Kubota®

**KUBOTA TRACTOR CORPORATION**

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: [kubotaUSA.com](http://kubotaUSA.com)



# Specifications

MODEL		M4N-071HDC12	M5N-091HDC12 (HDC24)	M5N-111HDC12 (HDC24)
Engine	Type (Make:KUBOTA)	V3800-TE4 – 4 cylinders in-line, Common Rail System, Direct Injection, DPF, DOC	V3800-TIEF4 4 cylinders in-line, Common Rail System, Direct Injection, DPF, DOC, SCR	
	No. of Cylinders / Aspiration	4 / Turbocharged	4 / Turbocharged w/Intercooler	
	Engine HP (SAE J 1349) [HP (kW)]	70.4 (52.5)	87.5 (65.2)	100.7 (75.1)
	PTO HP at Rated rpm (OECD CODE2) [HP (kW)]	61 (45.5)	HDC12: 78 (58.1); HDC24: 75 (55.9)	HDC12: 91 (67.9); HDC24: 88 (65.6)
	Total Displacement [cu. in. (cc)]	230 (3769)		
	Rated Speed [RPM]	2400	2600	
	Fuel Tank Capacity [gal. (ℓ)]	20.1 (76)		
	Alternator	100 Amp (Opt 130 Amp)	80 Amp (Opt 130 Amp)	
Transmission	No. of Speeds (Option)	F12 / R12 (F18 / R18 w/creep)	HDC12: F12 / R12 (F18 / R18 w/creep); HDC24: F24 / R24 (F36 / R36 w/creep)	
	Main Gear Shift	6 Speeds Synchronized		
	Range Gear Shift	High / Low Range Gear Shift		
	Shuttle Shift	Electro Hydraulic Shuttle		
	Dual Speeds (Hi - Lo)	N/A	HDC12: N/A; HDC24: Std	
	Max. Traveling Speed [mph (km/h)]	22.2 (35.5)	HDC12: 22.2 (35.5) HDC24: 21.9 (35.1)	HDC12: 22.2 (35.5) HDC24: 21.9 (35.1)
	Brake Type	Hydraulic wet disc		
Four Wheel Brake	Std			
PTO	Type	Live-independent PTO, electro-hydraulic clutch with brake		
	PTO Speed [rpm]	540 / 540E		
Hydraulics	System	Open Center		
	Pump Capacity (3-Point Hitch) [gpm (ℓ/min)]	23 (87.2)	24.9 (94.5)	
	3-point Hitch	Telescopic Stabilizers		
	Control System	Position, Draft (Top link sensing)		
	Category	II		
	Lift capacity at 24 in. behind lift point (OECD)* [lbs. (kg)]	3307 (1500)		
No. of Remote Valves	2 (Max 5)			
Other Features	4WD Drive System	Bevel Gear Type		
	Steering	Hydraulic Power Steering		
	Tilt Steering	Standard		
	Hood Type / Pedal Type	Full open, Slanted, Steel / Hanging		
	Panel Type	Electronic		
	Seat	with Reclining, Arm Rest		
	RPM Memory	Standard		
Standard Tire Size	Front	8.0 - 16		
	Rear	12.4 - 24		
Dimensions and Weight	Overall Length [in. (mm)]	149.2 (3790)	155.5 (3950)	
	Overall Height Top of CAB [in. (mm)]	90.2 (2290)		
	Overall Width (Left Step to end of Right fender) [in. (mm)]	53.9 (1370)		
	Wheelbase [in. (mm)]	83.9 (2130)		
	Crop Clearance (Front Axle) [in. (mm)]	14.6 (370)		
	Turning Radius (w/o brake, w/Hi Speed) [ft. (m)]	12.5 (3.8)		
Weight [lbs. (kg)]	5291 (2400)	5622 (2550)		

\*At lower link end with links horizontal



## KUBOTA TRACTOR CORPORATION

Kubota Tractor Corporation, 3401 Del Amo Boulevard, Torrance CA 90503  
 Western Division: 1175 S. Guild Ave., Lodi, CA 95240 Tel (209) 334-9910  
 Central Division: 14855 FAA Boulevard, Fort Worth, Tx 76155 Tel (817) 571-0900  
 Northern Division: 6300 at One Kubota Way, Groveport, OH 43125 Tel (614) 835-1100  
 Southeast Division: 1025 Northbrook Parkway, Suwanee, GA 30024 Tel (770) 995-8855

Visit our web site at: [www.kubota.com](http://www.kubota.com)

