

# T80 Series

# Specifications

T1880 - T2080 - T2380



Model		T1880A2	T2080A2	T2380A2
Engine:	Model	GH541V	GH737V	GH738V
	Type	OHV air-cooled gasoline engine		
	Number of cylinders	1	2	
	Total displacement	36.4 cu.in. (597 cc)	44.2 cu.in. (725 cc)	
	Gross horse power	18 HP (13.4 kW)*	20 HP (14.9 kW)*	22 HP (16.4 kW)*
	Starter	Electric start		
Battery voltage:		12V		
Fuel tank capacity:		3.6 gal. (13.5 l)		
Dimensions:	Overall length	77.0 in. (1955 mm)		
	Overall width [with mower]	54.8 in. (1392 mm)	60.8 in. (1544 mm)	
		[42" mower]	[48" mower]	
	Overall height	42.9 in. (1090 mm)	44.3 in. (1125 mm)	
Wheelbase:		50.8 in. (1290 mm)	54.3 in. (1380 mm)	
Wheel tread:	Front	30.8 in. (783 mm)		
	Rear	28.6 in. (727 mm)		
Tire size:	Front	15×6.00–6		
	Rear	22×11.00–10		
Weight:		639 lbs. (290 kg) (with 42" mower deck)	650 lbs. (295 kg) (with 42" mower deck)	661 lbs. (300 kg) (with 48" mower deck)
Turning radius (at outer front tire):		6.3 ft. (1.9 m)		
Steering system:		Pinion & Sector gear type		
Number of speeds:		Infinite to maximum		
Traveling speed:	Forward	0 to 5.6 mph (0 to 9.0 km/h)		
Transmission:		Hydrostatic transmission		
PTO clutch:		Belt tension		
Brake:		Disc		
KRA system:		Standard		
Optional accessories:		Hour meter, Tractor cover, etc.		

## Mower Specifications

Model	RCK42-LT20-2	RCK48-LT23-2
Mounting method	Suspended parallel linkage	
Adjustment of cutting height	Dial gauge	
Cutting width	42 in. (1067 mm)	48 in. (1219 mm)
Cutting height	1.0–4.0 in. (25 to 102 mm)	
Number of blades	2	
Discharge	Right side	

\*Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information.